

put X in box of item you want

FAX 480-503-3834 EMAIL info@brycefastener.com

Order	Quote											
Security drive √	Material √	Head √		Thread				Length √		Quantity	Price	Exten.
				Machine √	Sheet mtl							
Keyed-lok®	Stainless	Button		2/56.		#2		1/4.				
Penta-plus™	Alloy black	Flat		4/40.		#4		3/8.				
Penta bolt	Zinc plated			6/32.		#6		1/2.				
Hex-pin				8/32.		#8		5/8.				
Tam-6lobe™				10/24.		#10		3/4.				
Spin-lok™				10/32.		#12		1				
Penta nut™				12/24.		#14		1 1/4.				
				1/4-20.				1 1/2.				
bit tips :see below								1/4-28.				
				5/16-18.				2 1/4.				
				3/8-16.				2 1/2.				
				1/2-13.				3				
				5/8-11.				3 1/2.				
				Metric				Metric				
				M2				6				
				M2.5				8				
				M3				10				
				M4				12				
				M5				16				
				M6				20				
				M8				25				
				M10				30				
				M12				35				
				M14				40				
				M16				50				
								60				

BIT TIPS

KEYED-LOK®	PENTA-PLUS™	PENTA SKT	HEX-PIN™	L WRENCH	TORX®(TAM 6 LOBE™)
1GBU02	P-02	7/8.	3/32.	3/32.	T-8
1GBU04	P-04		1/8.	1/8.	T-10
1GBU06	P-1		5/32.	5/32.	T-15
1GBU10	P-2		3/16.	3/16.	T-20
1GBU25	TV MOUNT S		7/32.	7/32.	T-25
1GBU31	TV MOUNT L		1/4.	1/4.	T-27
1GBU50	P-3		5/16.	5/16.	T-30
	P-4				T-40
					T-45
					T-50

NAME	if you are using a credit card:		to email #
CO:	Type		1st 4#
address	#		2nd4#
	Exp		
	Name		3rd4#
			4th4#
	po #		
tel #	shipping method		
fax#			